



PRO-SW3000XL



For swing gates up to 16 ft. (11.3 m) long and 650 lbs. (294.8 kg) per leaf.

For over twenty years we have been offering automated gate systems designed to fit our customers needs and lifestyles.

COMMERCIAL

ESTATE

RESIDENTIAL

AGRICULTURAL



Available from:

2-YEAR WARRANTY



Includes battery backup, radio receiver, transmitter, AC transformer, and all necessary mounting hardware for a standard post mount installation, 14" (36 cm) offset.



PRO-SW3000XL

COMMERCIAL

ESTATE

RESIDENTIAL

AGRICULTURAL

The PRO-SW3000XL/3200XL will operate a gate up to 16' (4.9 m) long and weighing 650 lbs. (294.8 kg) each leaf; if all proper installation procedures have been followed. Ball bearing hinges should be used on all gates weighing over 250 lbs (113.4 kg).

FEATURES

- Extended Cycle Life - Enhanced motor design makes this operator ideal for today's single family estates, housing complexes of up to twenty multi-family units or equivalent commercial applications
- Features GTO/PRO's true soft start and stop operation. **Open and close times from 15 seconds.**
- Full systems capable, single/dual control board includes an adjustable obstruction sensing, gate sequencing, and auto close settings.
- U.L. rated for Class I, II, III & IV. System certified to be in compliance with U.L. 325, 5th edition.

CONTROLS

- The GTO/PRO® control board can be programmed for pull-to-open or push-to-open.
- Adjustable auto close, obstruction sensitivity and dual gate sequencing.
- One button auto-memorization of digital transmitter code.
- Charging regulated circuit on control board. "Sleep draw" is 40 mA; "active draw" is 2 to 9 amps.
- GTO/PRO® remote-mounted 318 MHz RF receiver and one button transmitter. included

OPTIONS:

Solar Panel Charger: float voltage 14.5 V DC output from a 19-3/8" (49.21 cm) x 15 1/4" (38.74 cm) silicon alloy panel. Generates minimum of 10 watts at 600 mA. A gated diode on the control board prevents battery discharge. (FM123)

PRO-SW3200XL Designed to work as a slave gate operator in dual gate applications when combined with a PRO-SW3000X. Includes a 40' (12.2m) power cable.

Push to open applications: Require one (349IH) bracket per operator.

DRIVE

Powered by: a reliable 12 Volt (120 Watt) DC motor, 16:1 planetary gear drive system.

Temperature rating: -5°F (-28°C) to +160°F (71°C). Battery rating

Opening time: From 15 seconds.

Range of arm stroke: is up to 16" (41 cm).

Operator length with arm fully retracted is 40.25" (102 cm), mounting point to mounting point.

POWER

The PRO-SW3000XL system is powered by one 12 Volt DC / 7.0 amp hour, sealed, rechargeable battery (included). Battery charge is maintained by a 120V AC/60 Htz input and 18V AC at 40 VA. output transformer rectified, to 14V DC through control board.

SUGGESTED ACCESSORIES:

- Automatic Gate Lock (FM144/FM142)
- Estate Intercom/Keypad (F4100MLB)
- Gooseneck Pedestal (F100/F110)
- Driveway Exit Wand (F140)
- Solar Panel (FM122/FM123)
- Keychain Transmitter (RB742)
- Digital Keypad (F310)
- Loop Detector (LOOPDT1)
- Preformed Loops (L-SC-0408/0612, L-PO-0408/0612)